

EMC CLARiiON CX300 Networked Storage System

Specifications

RAID Levels

RAID 0: Data striped across three to 16 drives

RAID 1: Mirrored pairs of two drives

RAID 1/0: Data mirrored, then striped across four to 16 drives

RAID 3: Independent data access on five or nine drives (with dedicated parity disk)

RAID 5: Independent data access on three to 16 drives (with striped parity)

Any combination of these RAID levels can exist on a single CX300

RAID stripe depth configurable to 4, 16, 64, 128, or 256 sectors per disk

MetaLUNs: Storage virtualization via online LUN expansion through either striping or concatenation

Rebuild priority tuning: adjustment of minimum I/O reserved for server use during rebuild

Configurable global hot spares

Front-End (Host) Connectivity

Two storage processors per CX300

Each storage processor has two 2 Gb Fibre Channel optical ports.

FCP SCSI-3 protocol

Command tag queuing up to 256 tags

FC-AL and FC-SW support

Maximum Cable Length

Shortwave Optical: 300 meters (2 Gb), 500 meters (1 Gb)

Back-End (Disk) Connectivity

Each storage processor has one 2 Gb Fibre Channel Arbitrated Loop. CX300 supports a maximum of 60 disk drives.

Drive Interface

Failover from each storage processor to both Fibre Channel loops is possible

	36 GB (15,000)	73 GB (15,000)	73 GB (10,000)	146 GB (10,000)	250 GB ATA (5,400)
Formatted Capacity					
(520 bytes/sector, 1 MB = 1,000,000 bytes)	36.01 GB	72.67 GB	72.67 GB	145.78 GB	251 GB
Form Factor	3.5"	3.5"	3.5"	3.5"	3.5"
Height	1.0"	1.0"	1.0"	1.0"	1.0"
Rotational Speed	15,000 rpm	15,000 rpm	10,000 rpm	10,000 rpm	5,400 rpm
Interface	Fibre Channel	Fibre Channel	Fibre Channel	Fibre Channel	ATA
Data Buffer	16 MB	16 MB	16 MB	32 MB	2 MB
Transfer Rates					
Buffer to/from Media	51-69 MB/s	57-86 MB/s	26.7-40.2 MB/s	43-78 MB/s	26-50 MB/s
SP to/from Buffer	200 MB/s (max.)	200 MB/s (max.)	200 MB/s (max.)	200 MB/s (max.)	133 MB/s (max.)
Access Time					
Average Seek	3.6 ms Read 4.2 ms Write	3.6 ms Read 4.0 ms Write	5.2 ms Read 6.2 ms Write	4.7 ms Read 5.3 ms Write	12 ms Read 13 ms Write
Rotational Latency	2 ms	2 ms	2.99 ms	2.99 ms	5.5 ms

Available Software

Navisphere® Manager: comprehensive configuration, management, and event notification for single or multiple CLARiiON systems

Navisphere Analyzer: comprehensive performance, management, and trends analysis

SnapView™: point-in-time view of information for non-disruptive backup and BCVs

PowerPath™ Base: path failover for continuous data access

PowerPath: path failover for continuous data access and load balancing for optimal channel performance

Nondisruptive Upgrade (NDU): online upgrades of storage software and microcode

CLARAlert®: constant system monitoring and remote diagnostics

* Consult your EMC account manager for availability, software configuration, and compatibility information.

CLARiiON CX systems can be integral elements of a comprehensive information lifecycle management strategy—a strategy that helps your enterprise attain the maximum value from its information, at the lowest TCO, at every point in the information lifecycle. Information lifecycle management maps the right service level to the right application at the right cost—at the right time.



Dimensions (approximate)

Rackmount Processor Chassis with Standby Power Supplies (standard NEMA 19-inch rack)

Height	Width	Depth	Weight
6.83 in. (1736 cm), 4 EIA units	17.72 in. (45.0 cm)	23.75 in. (60.38 cm)	164.1 lb. (74.6 kg) max.

Rackmount 2 Gbit Fibre Channel Disk Expansion Chassis with Dual Power Supplies

Height	Width	Depth	Weight
5.25 in. (13.33 cm), 3 EIA units	17.72 in. (45.0 cm)	23.75 in. (60.38 cm)	88 lb. (40 kg) max. configuration

Rackmount ATA Disk Expansion Chassis with Dual Power Supplies

Height	Width	Depth	Weight
5.25 in. (13.33 cm), 3 EIA units	17.72 in. (45.0 cm)	23.75 in. (60.38 cm)	84 lb. (38 kg) max. configuration

40U Rack Enclosure

Height	Width	Depth	Weight
75.0 in. (190.8 cm)	24.0 in. (61.1 cm)	36.0 in. (91.6 cm)	Empty: 300 lb. (136 kg)

Power

	Processor Chassis	2Gbit Fibre Channel Disk Expansion Chassis	ATA Disk Expansion Chassis
Frequency	47-63 Hz	47-63 Hz	47-63 Hz
AC Voltage	90-264 Vrms, single phase	90-264 Vrms, single phase	90-264 Vrms, single phase
Power Factor	.98 (min)	.98 (min)	.98 (min)
Power Consumption (maximum)	650 VA, 618W	400 VA, 392W	300 VA, 294W
Heat Dissipation (maximum)	2,000 BTU/hour	1,340 BTU/hour	1,017 BTU/hour
Protection	Rackmount: 10 amps, fused	Rackmount: 10 amps, fused	Rackmount: 10 amps, fused
AC Circuits	Redundant, external AC circuits	Redundant, external AC circuits	Redundant, external AC circuits
Inlet Type	Dual Inlet Rackmount: IE320-C14 appliance coupler	Dual Inlet Rackmount: IE320-C14 appliance coupler	Dual Inlet Rackmount: IE320-C14 appliance coupler

AC Power Capability

40U Cabinet (optional)

Dual Inlets
NEMA L6-30P or IEC309-332 P6 or IP-57 (Australia)
200-240 VAC +/- 10%, Single Phase
47-63 Hz
4800 VA @ 200 V, 5760 VA @ 240 V
30A, 2-pole circuit breaker

Operating Environment

Temperature: 50-104 degrees F (10-40 degrees C)
Temperature Gradient: 10 degrees C/hr
Relative Humidity: 20% to 80% (non-condensing)

Altitude

8,000 ft. (2438.4 m) @ 104 degrees F (40 degrees C) max.
10,000 ft. (3048 m) @ 98.6 degrees F (37 degrees C) max.

Electromagnetic Emissions and Immunity

FCC Class A	EN55022 Class A
CE Mark	VCCI Class A (for Japan)
ICES-003 Class A (for Canada)	AS/NZS 3548 Class A (for Australia/New Zealand)
EN55024 Immunity, ITE	BSMI Class A (for Taiwan)

Quality and Safety Standards

UL 1950; CSA C22.2-950; EN60950
NEBS Level 3 Certification planned for April, 2004
Manufactured under an ISO 9000-registered quality system



EMC Corporation
Hopkinton
Massachusetts
01748-9103
1-508-435-1000
In North America 1-866-464-7381

EMC², EMC, CLARiiON, CLARAlert, Navisphere, PowerPath, and where information lives are registered trademarks of EMC Corporation. Other trademarks are the property of their respective owners.

©2002, 2004 EMC Corporation. All rights reserved.
Produced in the USA. 1/04

Specification Sheet
C1078